



PRODUCT NUMBER: 2095301

POWERCOAT® 953-01 Nitrif

Mechanical and chemical resistance to a large range of products (oils, detergents and many solvents).

Preparation of greasy products, production of paints, varnishes.

Honeywell

Overview

Reference Number

2095301

Product Type

Gloves

Range

Chemical Protection

Line

Heavy chemical

Brand

Honeywell

Brand formerly known as

SPERIAN

Industry

- Agriculture
- Automotive and Part Manufacturer
- Aviation
- Building and Construction
- Catering
- Chemical Industries
- Food Industries
- Industrial Cleaning
- Iron and steel industry
- Maintenance
- Offshore
- Petro-chemical
- Printing Industries
- Services
- Ship Building
- Transportation
- Utilities
- Water treatment

Product Use

Mechanical and chemical resistance to a large range of products (oils, detergents and many solvents). Food preparation of greasy products, production of paints, varnishes.

Features & Benefits

Feature

Unsupported nitrile glove

Cotton flock inside

Diamond-pattern finish

Benefit

COMFORT

The glove's nitrile formula has been selected to give great elasticity to the glove.

The cotton flocked interior provides the user with greater comfort.
Its diamond finish is tailored for grasping dry and damp objects.

RESISTANCE

Nitrile ensures good chemical properties and excellent mechanical characteristics (abrasion).
It is particularly suitable for the handling of oils and greases.
Avoid contact with solvents containing ketones.

SAFETY

Category III glove for constant quality.
Its long cuff helps to protect the forearm.

Technical Description

Description

CE CATEGORY : III Irreversible risks
 In accordance with standards :
 EN 420-2003 EEC Basic standards
 EN 388-2016 Mechanical risks
 EN ISO 374-1:2016 Chemical risks
 EN ISO 374-5:2016 Micro organisms

CHARACTERISTICS :

Unsupported nitrile glove
 Cotton flock inside
 Diamond-pattern finish

Product Technology

Dipped Gloves

Glove/liner color

Green

Coating Type

Nitrile and cotton

Length

33 cm

Thickness

0.4 mm

Harmlessness

In conformity with European standards

Dexterity

Class 5

Sizes

7 to 12

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	4
Cutting resistance (Coupe test)	1
Tear resistance	0
Puncture resistance	1
Cutting resistance (TDM test)	X

EN ISO 374-1 Resistance to

Resistance to permeation by chemicals	Type A - AJKLMNOT
---------------------------------------	-------------------

EN 374-3 Resistance to

Resistance to permeation by chemicals	JKL
---------------------------------------	-----

Certifications

EU Category PPE

3

EU Certification

0075/797/162/07/18/1422

Additional Information

User Manual

UI 104

User Information Sheet

104

Maintenance

Storage Information

Individual packaging.

Minimum sale packaging 10 pairs.

Boxes of 100 pairs.

Care Instructions

In order to keep its properties, this article should not be cleaned.